

InterBox Housing



Description

The galvanized steel sheet housing *InterBox* is characterized by the following design features:

- ✓ Flexible design in all three axes to realize individual customer requirements.
- ✓ Easy assembly due to its simple setting.
- ✓ Multipurpose applications like:
 - 19" unit
 - desktop enclosure
 - installation housing optionally for flange angle or DIN rail.
- ✓ EMC-compatible design realized by contact pins.
- ✓ Protection classes up to IP 40.
- ✓ Besides the standard varnish also individual color variations are available.
- ✓ Additional imprints according to customer requirements are available.

Material: Galvanized sheet steel

Surface: RAL 9006 - white aluminium or
RAL 9005 - black

Set Consists of:

- 1 top-shell
- 1 bottom-shell
- 4 countersunk screws

Delivery:

The *InterBox* housing will be delivered fully assembled and painted.

Order details *InterBox* housing

Version	height [mm]	width [mm]	depth [mm]	RAL 9005 order no. 409.	RAL 9006 order no. 409.
1	59	200	205	138 056	138 057
2	44,45 (1TE)	200	205	138 058	138 059
3	44,45 (1TE)	300	300	138 060	138 061

Accessories	order no. 409.
Housing foot 12,7 x 12,7 x 3,1[mm] PU, black	137 981
Housing foot 12,7 x 12,7 x 5,8[mm] PU, black	137 982
DIN rail clip (only for Version 1 - 2)	137 493
19" flange angle	on request